



The **Swingmatic Slic** is ideal for situations that may be exposed to weather such as a porch door. The separate power unit needs to be installed in a completely dry environment but the mechanism can withstand damp but not exposed conditions. The Slic also has a unique anti-crushing device ensuring ease of use and giving it an additional safety factor. Please call on +44 (0) 01273 693393 to discuss your particular needs.

- Simple installation
- Robust drive unit with 24vdc geared motor
- Anti-crushing device during opening & closing cycles with adjustable motor cut out delay
- Easy to open & close door manually if power fails
- Adjustable articulated operating arm or slide arm option
- Wide choice of actuators – eg PIR's Pusbuttons etc.
- Remote control (extra)
- Battery back up (extra)
- Electric lock interface
- Automatic door closing options with variable time delay
- Guaranteed 3 years
- Door Leaf – width 1200mm weight 120kgs
- Suitable for single & double leaf doors

TECHNICAL INFORMATION

Technical Data -Drive Unit

WEIGHT 4kgs
SIZE L432mm x H100mm x D85 mm
MOTOR RATED 15w
MOTOR VOLTAGE 24vdc
POWER FOR EXTERNAL ACCESSORIES 24vdc

Technical Data -Power supply

WEIGHT 1kg
SIZE L120mm H100mm D85mm
INPUT VOLTAGE 240vac
OUTPUT VOLTAGE 18vac

Adjustable Parameters

OPENING ANGLE 60–120°
HOLD OPEN TIME 0–60 secs
Microswitches for opening & closing positions
Torque limiter for anti-crushing device

OPERATING CYCLE > (unlock) > open > stop > (hold open) > close > stop > (lock)

Full range of accessories available upon request. For more information please contact:

TEL & FAX **+44(0)1273 693393** E-MAIL **sales@adcswingmatic.com**

Advanced Door Controls Ltd 1c Bonchurch Road Brighton East Sussex BN2 3PJ England